


## Rodamiento conico 620-612-TIMKEN - 620-612-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/620-612-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
39.687	120.650	41.275	20700	0.31	5300	20900	1.86	24000	620 612	
1.5625	4.7500	1.6250	4660		12100	9318		54000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>1</sub> <sup>(2)</sup>	Backing Shoulder Dia. d <sub>s</sub> <sup>(3)</sup>	Max Housing Fillet Radius r <sub>1</sub> <sup>(2)</sup>	Backing Shoulder Dia. D <sub>s</sub> <sup>(3)</sup>	Cage A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(4)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg		
41.275	31.350	-14.8	0.8	52.8	53.8	3.3	119.8	105.8	3.8	1.5	75.3	16.2	0.904	2.53
1.6250	1.2500	-0.55	0.03	2.05	2.09	0.13	4.33	4.12	0.15	0.08				5.58

### CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952312590
Diámetro interior	39.687 mm
Diámetro exterior	120.65 mm
Espesor	41.275 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE