

Rodamiento conico

HM903245-HM903210-TIMKEN - HM903245-HM903210-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/hm903245-hm903210-timken>

TAPERED ROLLER BEARINGS																	
SINGLE-ROW • TYPE TS																	
TYPE TS																	
Bearing Dimensions										Part Number							
Load Ratings										Inner		Outer					
Bore d	O.D. D		Width T	Dynamic ⁽¹⁾ C ₁₀		Factors ⁽²⁾ e	Dynamic ⁽¹⁾ C ₉₀		Factors ⁽²⁾ k	Static C ₁₀	10	10	10				
mm	mm	mm	mm	N	lbf		N	lbf		N	lbf						
41.275	95.250	30.958	130.000	130000	2910	0.24	35400	44800	0.79	133000		HMM30245	HMM30210				
1.6250	3.7500	1.2188	5.1181	32010	6500		7990	10100		28700							
Bearing Dimensions																	
Shaft										Geometry Factors ⁽³⁾							
Width B		Width C		EF, C ₂ y ⁽⁴⁾		Max Shaft Fillet Radius R _S		Backing Shoulder Dia. d ₁		Max Housing Fillet Radius R _H		Backing Shoulder Dia. d ₂					
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
28.575	22.225	8.5	3.5	54.0	62.0	0.8	91.0	81.0	3.9	2.1	33.7	12.4	0.1010				
1.1250	0.8750	0.335	0.138	2.14	2.44	0.031	3.58	3.19	0.156	0.083			1.04				
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				
28.575	22.225	8.5	3.5	54.0	62.0	0.8	91.0	81.0	3.9	2.1	33.7	12.4	0.1010				
1.1250	0.8750	0.335	0.138	2.14	2.44	0.031	3.58	3.19	0.156	0.083			1.04				

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952313313
Diámetro interior	41.275 mm
Diámetro exterior	95.25 mm
Espesor	30.958 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE