


Rodamiento conico 365S-362X-TIMKEN - 365S-362X-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/365s-362x-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|--------|---------|---------------------------------------|-------------------------|---------------------------------------|--------------------------------------|-----------------------|-------|-------------|------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factor ⁽²⁾ e ₂ | Static C ₃ | Inner | Outer | |
| mm | mm | mm | N | | N | N | N | | | |
| 49.212 | 90.000 | 25.001 | 102900 | 0.32 | 26400 | 14000 | 1.82 | 99000 | 365-S | 362X |
| 1.9375 | 3.5433 | 0.9843 | 22600 | | 5800 | 3250 | | 21900 | | |

| Bearing Dimensions | | | | | | | | | | Geometry Factors | | | Bearing Weight | |
|--------------------|---------|--------------------------|--|--------------------------------------|--|--------------------------------------|-------------------------------|-------------------------------|-------------------------------|------------------|----------------|----------------|----------------|----------------|
| Shaft | | | | | Housing | | | | | Cage | G ₁ | G ₂ | | C ₃ |
| Width B | Width C | ER. Dr. a ⁽¹⁾ | Max Shaft Fillet Radius R ⁽¹⁾ | Backing Shoulder Dia. d _s | Max Housing Fillet Radius r ⁽¹⁾ | Backing Shoulder Dia. D _s | A ₁ ⁽¹⁾ | A ₂ ⁽¹⁾ | A ₃ ⁽¹⁾ | | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | | |
| 22.225 | 25.000 | -4.3 | 0.8 | 54.0 | 55.0 | 2.0 | 84.0 | 80.0 | 0.4 | 1.1 | 33.0 | 14.0 | 0.0773 | 0.62 |
| 0.8750 | 0.9843 | -0.17 | 0.03 | 2.13 | 2.17 | 0.08 | 3.31 | 3.15 | 0.01 | 0.04 | | | | 1.36 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952315461 |
| Diámetro interior | 49.212 mm |
| Diámetro interior | 1 15/16" inch |
| Diámetro exterior | 90 mm |
| Diámetro exterior | 3.543" inch |
| Espesor | 25.001 mm |
| Espesor | 0.984" inch |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE