


## Rodamiento conico 65200-65500-TIMKEN - 65200-65500-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/65200-65500-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
52 800	127 800	44.450	242000	1.23	62100	52300	297000	65200	65500	
2.0300	5.0000	1.7500	54700		14200	11900	66700			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft		Housing		Cage					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>				A <sub>3</sub> <sup>(1)</sup>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm					
44.450	34.925	-5.4	3.5	68.8	25.8	3.3	119.8	107.8	4.1	1.1	85.2	17.2	0.9027	2.90
1.7500	1.3750	-0.37	0.14	2.72	2.95	0.13	4.89	4.21	0.16	0.05				6.38

### CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952316529
Diámetro interior	50.8 mm
Diámetro exterior	127 mm
Espesor	44.45 mm
Peso	2900 g
Envasado	-
Estándar	-

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE