


Rodamiento conico 622A-612A-TIMKEN - 622A-612A-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/622a-612a-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ Y	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ X	Static C ₀	Inner	Outer		
mm	mm	mm	N		N		N				
55.006	120.040	41.275	201900	0.31	1.01	53900	20900	1.66	244000	622A	612A
2.1850	4.7260	1.6250	48500			12100	6510		54800		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R ⁽¹⁾	Backing Shoulder Dia. d ₁	Backing Shoulder Dia. d ₂	Max Housing Fillet Radius r ⁽¹⁾	Backing Shoulder Dia. D ₁	Backing Shoulder Dia. D ₂	Cage A ₁ ⁽¹⁾	Cage A ₂ ⁽¹⁾	G ₁	G ₂		C ₃
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg
41.275	31.750	-14.6	0.8	64.8	65.8	3.3	119.8	100.0	3.8	1.9	75.9	16.2	0.0064	2.13
1.6250	1.2500	-0.58	0.03	2.52	2.58	0.13	4.33	4.06	0.15	0.09				4.72

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952317595
Diámetro interior	55.006 mm
Diámetro exterior	120.04 mm
Espesor	41.275 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE