


## Rodamiento conico 65237A-65500-TIMKEN - 65237A-65500-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/65237a-65500-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |         |         | Load Ratings                          |                         |                                       |                         |                       |        | Part Number |  |
|--------------------|---------|---------|---------------------------------------|-------------------------|---------------------------------------|-------------------------|-----------------------|--------|-------------|--|
| Bore d             | O.D. D  | Width B | Dynamic <sup>(1)</sup> C <sub>1</sub> | Factor <sup>(2)</sup> e | Dynamic <sup>(1)</sup> C <sub>2</sub> | Factor <sup>(2)</sup> K | Static C <sub>3</sub> | Inner  | Outer       |  |
| mm                 | mm      | mm      | N                                     |                         | N                                     |                         | N                     |        |             |  |
| 60.325             | 127.000 | 44.450  | 242000                                | 1.23                    | 62100                                 | 52700                   | 297000                | 65237A | 65500       |  |
| 2.3750             | 5.0000  | 1.7500  | 54700                                 |                         | 14200                                 | 11900                   | 66700                 |        |             |  |

| Bearing Dimensions |        |                          |      |       |      |         |       |       |      | Geometry Factors |                |                | Bearing Weight |      |
|--------------------|--------|--------------------------|------|-------|------|---------|-------|-------|------|------------------|----------------|----------------|----------------|------|
| Width B            |        | ER. Dr. a <sup>(1)</sup> |      | Shaft |      | Housing |       | Cage  |      | G <sub>1</sub>   | G <sub>2</sub> | C <sub>3</sub> |                |      |
| mm                 | mm     | mm                       | mm   | mm    | mm   | mm      | mm    | mm    | mm   |                  |                |                |                |      |
| 44.450             | 34.925 | -0.4                     | 1.5  | 71.1  | 78.8 | 3.3     | 119.8 | 107.8 | 4.1  | 1.1              | 85.2           | 17.2           | 0.9827         | 2.62 |
| 1.7500             | 1.3750 | -0.37                    | 0.06 | 2.80  | 3.07 | 0.13    | 4.89  | 4.21  | 0.16 | 0.05             |                |                |                | 5.78 |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | TIMKEN        |
| Nº Ean13          | 3663952318714 |
| Diámetro interior | 60.325 mm     |
| Diámetro exterior | 127 mm        |
| Espesor           | 44.45 mm      |
| Peso              | 2620 g        |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE