


Rodamiento conico 643-632-TIMKEN - 643-632-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/643-632-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽³⁾ C ₂	Factor ⁽⁴⁾ K	Static C ₃	Inner	Outer	
mm	mm	mm	N		N		N			
69.850	136.525	41.275	27600	2.29	71900	44000	1.61	29800	943	622
2.750	5.3750	1.6250	62100		18100	9960		67000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G ₁	G ₂		C ₃
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R ⁽²⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽³⁾	Backing Shoulder Dia. D _s	A ₁ ⁽⁴⁾	A ₂ ⁽⁵⁾	A ₃ ⁽⁶⁾					
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm					
41.275	31.750	-11.2	3.5	86.8	86.8	3.3	125.8	118.8	4.1	2.8	106.4	21.0	0.3814	2.81
1.6250	1.2500	-0.44	0.14	3.15	3.39	0.13	4.92	4.65	0.16	0.09				5.75

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952320663
Diámetro interior	69.85 mm
Diámetro interior	2 3/4" inch
Diámetro exterior	136.525 mm
Diámetro exterior	5 3/8" inch
Espesor	41.275 mm
Espesor	1 5/8" inch
Peso	2630 g
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE