

Rodamiento conico 644-632-TIMKEN - 644-632-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/644-632-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ^{1/3} C ₁	Factor ^{1/3} e	Dynamic ^{1/3} C ₂	Factor ^{1/3} C _{2e}	Static C ₃	Inner	Outer	
mm	mm	mm	N		N	N	N			
71.437	136.525	41.275	27600	0.30	71900	46600	1.61	29800	644 632	
2.8125	5.3750	1.6250	62100		18100	9980		87000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width		ER. Dr. a ^{1/2}	Shaft		Housing		Cage		G ₁	G ₂	C ₃			
B	C		Max Shaft Fillet Radius R ₁	Backing Shoulder Dia. d ₁	Max Housing Fillet Radius r ^{1/2}	Backing Shoulder Dia. D ₁	A ₁ ^{1/2}	A ₂ ^{1/2}						
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
41.275	31.290	-11.2	3.5	81.8	87.8	3.3	125.8	118.8	4.1	2.8	106.4	21.0	0.9814	2.96
1.6250	1.2500	-0.44	0.14	3.19	3.43	0.13	4.92	4.69	0.16	0.09				5.85

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952321066
Diámetro interior	71.437 mm
Diámetro exterior	136.525 mm
Espesor	41.275 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE