


Rodamiento conico 645X-632-TIMKEN - 645X-632-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/645x-632-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings							Part Number	
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂	Static C ₃	Factor ⁽²⁾ K	Static C ₄	Inner	Outer
mm	mm	mm	N		N		N		N		
71.437	136.525	41.275	22800	0.30	6900	3700	1.61	29800	640K	632	
2.8725	5.3750	1.6265	52400		13600	6920		67000			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R ⁽¹⁾	Backing Shoulder Dia. d ₁	Max Housing Fillet Radius r ⁽¹⁾	Backing Shoulder Dia. D ₁	A ₁ ⁽¹⁾	A ₂ ⁽¹⁾	Cage	G ₁	G ₂	C ₃		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
41.275	31.390	-11.2	6.4	82.7	55.8	3.3	125.8	118.8	4.1	2.8	106.4	21.0	0.3814	2.52
1.6265	1.2500	-0.44	0.25	3.25	2.22	0.13	4.92	4.65	0.16	0.09				5.58

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952321073
Diámetro interior	71.437 mm
Diámetro exterior	136.525 mm
Espesor	41.275 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE