


Rodamiento conico 6576-6525X-TIMKEN - 6576-6525X-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/6576-6525x-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings							Part Number	
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂	Static C ₃	Factor ⁽²⁾ K	Static C ₄	Inner	Outer
mm	mm	mm	N		N	N	N		N		
76.200	160.000	53.975	429000	0.80	136	114000	26900	1.46	523000	6576	6525X
3.0300	6.2950	2.1250	98500			25500	13900		118000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R ⁽¹⁾	Backing Shoulder Dia. d ₁	Backing Shoulder Dia. d ₂	Max Housing Fillet Radius r ⁽¹⁾	Backing Shoulder Dia. D ₁	Backing Shoulder Dia. D ₂	Cage A ₁ ⁽¹⁾	Cage A ₂ ⁽¹⁾	G ₁	G ₂		C ₁
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg
55.100	66.450	-13.2	3.5	92.8	95.8	3.0	153.4	161.8	4.1	6.9	106.6	33.6	0.1027	6.26
2.1693	1.7500	-0.52	0.14	3.62	3.80	0.12	6.04	6.55	0.16	0.24				11.80

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952321707
Diámetro interior	76.2 mm
Diámetro exterior	160 mm
Espesor	53.975 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE