

Rodamiento conico 685-672-TIMKEN - 685-672-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/685-672-timken>

| TAPERED ROLLER BEARINGS | | | | | | | | | | | |
|-------------------------|-----------|-----------------|--|-----------------------------------|--|-----------------------------------|-----------------|------------------|-------------|---------|----------------------------|
| SINGLE-ROW • TYPE TS | | | | | | | | | | | |
| TYPE TS | | | | | | | | | | | |
| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
| Bore d | O.D. D | Width T | Dynamic ⁽¹⁾ C_1 | Factor ⁽²⁾ e | Dynamic ⁽¹⁾ C_{10} | Factor ⁽²⁾ e_{10} | Static C_2 | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 98.425 | 168.275 | 41.275 | 20500 | 0.47 | 128 | 6800 | 95300 | 1.24 | 36000 | 605 612 | |
| 3.8750 | 6.6250 | 1.6250 | 59500 | | | 15400 | 12900 | | 88100 | | |
| Bearing Dimensions | | | | | | | | | | | |
| Shaft | | | Housing | | | Cage | | Geometry Factors | | | |
| Width B | Width C | ER. Dr. μm | Max Shaft Fillet Radius R_{fs} | Backing Shoulder Dia. d_s | Max Housing Fillet Radius r_{fs} | Backing Shoulder Dia. D_s | A_{10} | A_{11} | G_1 | G_2 | Bearing Weight C_3 |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | kg |
| 41.275 | 36.162 | -3.8 | 3.5 | 100.0 | 116.6 | 3.3 | 160.0 | 160.0 | 4.8 | 2.1 | 182.5 |
| 1.6250 | 1.1875 | -0.11 | 0.14 | 4.25 | 4.57 | 0.13 | 6.30 | 5.87 | 0.19 | 0.08 | 3.95 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952323916 |
| Diámetro interior | 98.425 mm |
| Diámetro exterior | 168.275 mm |
| Espesor | 41.275 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE