

Rodamiento conico H247535-H247510-TIMKEN - H247535-H247510-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/h247535-h247510-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁₀	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₉₀	Factor ⁽²⁾ K	Static C ₀	Inner	Outer		
mm	mm	mm	N		N		N				
200.025	384.175	112.712	147000	0.33	1.05	40000	247000	1.78	2110000	H247535	H247510
7.6750	15.1250	4.4375	377500			16000	558000		598000		

Bearing Dimensions											Geometry Factors			Bearing Weight
Shaft											Housing			
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R ₁	Backing Shoulder Dia. d ₁	Backing Shoulder Dia. d ₂	Max Housing Fillet Radius r ⁽¹⁾	Backing Shoulder Dia. D ₁	Backing Shoulder Dia. D ₂	A ₁ ⁽²⁾	A ₂ ⁽²⁾	G ₁	G ₂	C ₃	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
112.712	98.488	-27.8	6.4	231.0	241.0	6.4	302.5	346.0	19.2	2.8	194.4	148.4	0.1028	60.48
4.4375	3.5625	-1.10	0.25	9.05	9.49	0.25	14.27	13.82	0.40	0.12				133.34

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
N° Ean13	3663952327051
Diámetro interior	200.025 mm
Diámetro exterior	384.175 mm
Espesor	112.712 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE