


Rodamiento conico

M241549-M241510-TIMKEN - M241549-M241510-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/m241549-m241510-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factor ⁽²⁾ e ₂	Static C ₃	Inner	Outer	
mm	mm	mm	N		N	N	N			
204.788	292.100	57.945	60000	0.33	15000	89500	1.78	M241549	M241510	
0.0025	11.0000	2.2013	130000		20000	159000				

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G ₁	G ₂		C ₃
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R _{f1}	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ₁ ⁽¹⁾	Backing Shoulder Dia. D _s	Cage A ₁ ⁽¹⁾	A ₂ ⁽¹⁾	A ₃ ⁽¹⁾				G ₁	
57.945	46.696	-4.8	0.5	219.0	223.6	3.3	279.8	272.8	4.7	2.8	0.541	127.9	0.1279	15.85
2.2013	1.8125	-0.19	0.14	8.62	8.78	0.13	10.98	10.71	0.18	0.08				26.08

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952327235
Diámetro interior	204.788 mm
Diámetro exterior	292.1 mm
Espesor	57.945 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE