


Rodamiento conico H242649-H242610-TIMKEN - H242649-H242610-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/h242649-h242610-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽¹⁾ C ₀₂	Factor ⁽²⁾ K	Static C ₀	Inner	Outer	
mm	mm	mm	N		N		N			
206.375	336.550	98.425	130000	3.33	30100	29000	1.76	220000	H242649	H242610
8.1250	13.2500	3.8750	20000		7000	6000		52000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. α ⁽¹⁾	Max Shaft Fillet Radius R _{f1}	Backing Shoulder Dia. d _{1s}	Max Housing Fillet Radius r ₁ ⁽²⁾	Backing Shoulder Dia. D _{1s}	Backing Shoulder Dia. D _{2s}	A ₁ ⁽³⁾	A ₂ ⁽³⁾	A ₃ ⁽³⁾	G ₁	G ₂	C ₃	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				Std.
100.012	77.398	-25.4	3.3	227.0	231.0	3.3	218.0	206.0	11.1	1.8	1004.1	134.0	0.1405	33.19
3.9375	3.0625	-1.00	0.13	8.94	9.09	0.13	12.51	12.25	0.44	0.08				75.17

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952327297
Diámetro interior	206.375 mm
Diámetro exterior	336.55 mm
Espesor	98.425 mm
Peso	33200 g
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE