


Rodamiento conico

M246932-M246910-TIMKEN - M246932-M246910-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/m246932-m246910-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽³⁾ C ₂	Factor ⁽³⁾ C _{2e}	Static C ₀	Inner	Outer	
mm	mm	mm	N		N	N	N			
212.725	336.550	65.088	109000	0.32	20000	19000	1.78	M246932	M246910	
8.3750	13.2500	2.5625	177000		4000	2000				

Bearing Dimensions			Shaft				Housing				Cage			Geometry Factors			Bearing Weight
Width B	Width C	ER. Dr. a ⁽¹⁾	Max Shaft Fillet Radius R _f ⁽¹⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r _f ⁽²⁾	Backing Shoulder Dia. D _s	Max Housing Fillet Radius r _f ⁽²⁾	Backing Shoulder Dia. D _s	A ₁ ⁽³⁾	A ₂ ⁽³⁾	G ₁	G ₂	C ₃	kg			
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				lb			
65.088	95.800	-4.8	0.4	295.0	244.0	3.3	322.0	318.0	5.1	3.3	194.6	198.0	0.1408	21.86			
2.5625	2.5000	-0.19	0.25	9.25	9.61	0.13	12.68	12.32	0.20	0.13				48.17			

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952327389
Diámetro interior	212.725 mm
Diámetro interior	8 3/8" inch
Diámetro exterior	336.55 mm
Diámetro exterior	13 1/4" inch
Espesor	65.088 mm
Espesor	2 9/16" inch
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE