


## Rodamiento conico

### EE221026-221575-TIMKEN - EE221026-221575-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/ee221026-221575-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings					Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> C <sub>2e</sub>	Static C <sub>3</sub>	Inner	Outer
mm	mm	mm	N		N	N	N		
260.350	400.050	69.850	940000	0.30	240000	160000	1400000	EE221026	221575
10.200	15.750	2.750	213000		53000	37400	320000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>f1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(2)</sup>	A <sub>2</sub> <sup>(2)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	kg		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm		
67.475	46.638	0.8	0.7	280.0	206.6	6.4	371.5	366.0	14.3	5.6	1320.8	207.9	0.1467	26.74
2.663	1.8725	0.03	0.38	11.02	11.65	0.25	14.63	14.41	0.56	0.22				38.97

## CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952328584
Diámetro interior	260.35 mm
Diámetro exterior	400.05 mm
Espesor	69.85 mm
Invasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE