


Rodamiento conico

HM252348-HM252315-TIMKEN - HM252348-HM252315-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/hm252348-hm252315-timken>

TAPERED ROLLER BEARINGS
SINGLE ROW • TYPE TS

TYPE TS



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽³⁾ C ₁₀	Factor ⁽³⁾ C ₁₀ K	Static C ₂	Inner	Outer	
mm	mm	mm	N		N		N			
260.350	431.724	82.550	150000	0.33	30000	29100	1.78	260350	HM252315	
10.250	16.997	3.250	33700		61400	49700		40000	HM252315	

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G ₁	G ₂		C ₃
Width B	Width C	ER. Dr. α ⁽⁴⁾	Max Shaft Fillet Radius R ₁	Backing Shoulder Dia. d ₁	Max Housing Fillet Radius r ₁	Backing Shoulder Dia. D ₁	Backing Shoulder Dia. D ₂	A ₁ ⁽⁵⁾	A ₂ ⁽⁵⁾				A ₃ ⁽⁵⁾	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
79.71	68.325	-0.4	6.8	295.9	252.6	3.5	399.3	397.0	12.9	4.8	1504.3	147.8	0.1482	42.22
3.1408	2.370	-0.37	0.27	11.22	11.96	0.14	15.68	15.63	0.51	0.19				83.07

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952328638
Diámetro interior	260.35 mm
Diámetro interior	10 1/4" inch
Diámetro exterior	431.724 mm
Diámetro exterior	16.997" inch
Espesor	82.55 mm
Espesor	3 1/4" inch
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE