


Rodamiento de bolas una hilera ZKLN1545-2Z-INA - ZKLN1545-2Z-INA


<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/zkln1545-2z-ina>

Axial angular contact ball bearings ZKLN1545-2Z
double direction, gap seats on both sides



d	15 mm	Tolerance: -0.005
D	45 mm	Tolerance: -0.010
B	25 mm	Tolerance: -0.25
	60 °	Contact angle
D _{a max}	35 mm	
d _i	28 mm	
d _{h min}	20 mm	
r _{1 min}	0.6 mm	
r _{2 min}	0.3 mm	
m	0.21 kg	Mass
C _d	17900 N	Basic dynamic load rating, axial
C _{0d}	9500 N	Basic static load rating, axial
n _{Grease}	17500 r/min	Limiting speed for grease lubrication
M ₀	0.5 Nm	Bearing frictional torque
α ₀	±0.20 N/mm	Axial rigidity
α _{0d}	60 N/mmrad	Tilting rigidity
M ₀₂	0.102 kg x cm ²	Mass moment of inertia for rotating inner ring
	2 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM15	Designation of recommended INA locknut
	AM15	Designation of recommended INA locknut
		Locknuts not included in delivery.
M _s	10 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	5484 N	Axial preload force

Design of adjacent construction



CARACTERÍSTICAS DEL PRODUCTO

Marca	INA
Nº Ean13	3663952334851
Diámetro interior	15 mm
Diámetro interior	0.591" inch
Impermeabilización	Placa de protección en ambos lados
Diámetro exterior	45 mm
Diámetro exterior	1.772" inch
Espesor	25 mm
Espesor	0.984" inch
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE