




Rodamiento de bolas una hilera ZKLN2557-2Z-INA - ZKLN2557-2Z-INA

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/una-hilera/zkln2557-2z-ina>

Axial angular contact ball bearings ZKLN2557-2Z
double direction, gap seals on both sides

E	25 mm	Tolerance: -0.025
D	57 mm	Tolerance: -0.010
B	28 mm	Tolerance: -0.25
	60 °	Contact angle
D_{2max}	48 mm	
d₂	40.5 mm	
d_{2min}	32 mm	
r_{1min}	0.6 mm	
r_{2in}	0.3 mm	
m	0.34 kg	Mass
C_d	27500 N	Basic dynamic load rating, axial
C_{0a}	50000 N	Basic static load rating, axial
n_{Grease}	4700 1/min	Limiting speed for grease lubrication
M_{fr}	0.2 Nm	Bearing frictional torque
S_a	750 N/mm	Axial rigidity
S_t	200 1/mmrad	Tilting rigidity
M₂	0.486 kg x cm ²	Mass moment of inertia for rotating inner ring
	2 µm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM25	Designation of recommended INA locknut
	AM25	Designation of recommended INA locknut
		Locknuts not included in delivery.
M_s	25 Nm	Tightening torque
	9410 N	Only valid in conjunction with INA precision locknuts
		Axial preload force

CARACTERÍSTICAS DEL PRODUCTO

Marca	INA
Nº Ean13	3663952334882
Diámetro interior	25 mm
Impermeabilización	-
Diámetro exterior	57 mm
Espesor	28 mm
Envasado	-

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE