

Rodamiento conico 3188-3120-B-TIMKEN - 3188-3120-B-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/3188-3120-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|------|--|-----------------------------|--------------------------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₀ | Factors ⁽²⁾ K | Static C ₂ | Inner | Outer | |
| mm | mm | mm | N | | | N | | N | | | |
| 37.50 | 72.625 | 11.112 | 9400 | 0.22 | 1.80 | 2400 | 1.76 | 10200 | 3188 | 3120 B | |
| 1.250 | 2.850 | 0.4375 | 2300 | | | 500 | | 2500 | | | |

| Bearing Dimensions | | | | Shaft | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|--|-----------------------------------|--|--|--|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ D ₂ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | D ₁ | D ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | lbs |
| 20.807 | 22.812 | -18.2 | 77.268 | 4.202 | 0.8 | 26.5 | 48.8 | 88.8 | 23.4 | 8.8 | 0.2887 |
| 1.1910 | 0.9075 | -0.40 | 3.0433 | 0.1675 | 0.03 | 1.58 | 1.93 | | | | 1.34 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952335759 |
| Diámetro interior | 31.75 mm |
| Diámetro exterior | 72.625 mm |
| Espesor | 11.112 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE