

Rodamiento conico 16150-16284-B-TIMKEN - 16150-16284-B-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/16150-16284-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|---|-----------------------------|---|-----------------------------|--------------------------|-------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁₀ | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C ₉₀ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 38.100 | 72.238 | 8.733 | 16000 | 0.14 | 14700 | 19100 | 1.45 | 62800 | 16150 | 16284-B | |
| 1.5000 | 2.8440 | 0.3438 | 12700 | | 3000 | 2270 | | 14800 | | | |

| Bearing Dimensions | | | | Shaft | | Housing | | Geometry Factors | | | Bearing Weight | |
|--------------------|------------|-------------------------------|--|-----------------------------------|--|--|--|------------------|----------------|-----------------|----------------|------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ D ₂ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | D ₁ | D ₂ | C ₁₀ | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | kg | |
| 38.100 | 16.875 | -4.1 | 70.000 | 3.910 | 3.3 | 42.6 | 48.5 | 69.8 | 29.3 | 14.5 | 0.0707 | 0.37 |
| 0.8125 | 0.6625 | -0.16 | 2.7980 | 0.1563 | 0.14 | 1.69 | 1.95 | 2.72 | | | | 0.81 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952336558 |
| Diámetro interior | 38.1 mm |
| Diámetro exterior | 72.238 mm |
| Espesor | 8.7333 mm |
| Peso | 388 g |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE