

Rodamiento conico 44158-44348-B-TIMKEN - 44158-44348-B-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/44158-44348-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|--|-----------------------------|--------------------------|-------|-------|-------------|---------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factors ⁽²⁾ e | Static C ₀ | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 39.687 | 88.500 | 13.492 | 10900 | 0.17 | 0.17 | 22900 | 34000 | 0.75 | 80000 | 44158 | 44348-B |
| 1.5625 | 3.4843 | 0.5312 | 23400 | | 5810 | 8770 | 19000 | | 19900 | | |

| Bearing Dimensions | | | | Shaft | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|---|-----------------------------------|--|--|--|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Flange O.D. D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Seating Shoulder Dia. d ₁ | Seating Shoulder Dia. D ₁ | G ₁ | G ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | | | | lbs |
| 13.492 | 17.462 | 2.3 | 93.027 | 9.395 | 3.3 | 98.8 | 98.8 | 22.9 | 0.7 | 0.0089 | 0.75 |
| 0.5312 | 0.6875 | 0.09 | 3.6983 | 0.2187 | 0.14 | 2.00 | 2.28 | | | | 1.58 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952336633 |
| Diámetro interior | 39.687 mm |
| Diámetro interior | 1 9/16" inch |
| Diámetro exterior | 88.5 mm |
| Diámetro exterior | 3.484" inch |
| Espesor | 13.492 mm |
| Espesor | 17/32" inch |
| Peso | 730 g |
| Envasado | 1 |
| Estándar | Ninguna norma |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE