


Rodamiento conico

X30308UM-YSA30308RM-TIMKEN - X30308UM-YSA30308RM-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/x30308um-ysa30308rm-timken>

TAPERED ROLLER BEARINGS

TYPE TSF



Bearing Dimensions				Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factors ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factors ⁽²⁾ K	Static C ₀	Inner	Outer		
mm	mm	mm	N		N		N				
40.300	90.000	18.250	102000	0.35	20800	10000	108000	X30308UM	YSA30308RM		
1.5748	3.5433	0.4228	22200		6020	3950	24600				

Bearing Dimensions				Shaft			Housing		Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a ⁽³⁾	Outer Ring Range D ₁	Flange Width C ₁	Max Shaft File Radius (R ⁽⁴⁾)	Seaking Shoulder Dia. d ₁	Beading Shoulder Dia. D ₁	G ₁	G ₂	C ₃	kg	
mm	mm	mm	mm	mm	mm	mm	mm				lbs	
23.000	23.000	-4.8	90.000	9.000	2.2	36.0	93.0	31.8	15.4	0.0775	0.77	
0.9055	0.9014	-0.23	3.7195	0.1969	0.08	1.37	2.08				1.68	

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952336725
Diámetro interior	40 mm
Diámetro exterior	90 mm
Espesor	23 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE