

Rodamiento conico 44162-44348-B-TIMKEN - 44162-44348-B-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/44162-44348-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|--|-----------------------------|--|-----------------------------|--------------------------|-------------|---------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C ₃ | Factors ⁽²⁾ e | Static C ₀ | Inner | Outer |
| mm | mm | mm | N | | N | | N | | N | | |
| 41.275 | 88.500 | 13.462 | 10000 | 0.75 | 22000 | 34000 | 36000 | 0.75 | 30000 | 44162 | 44348-B |
| 1.6250 | 3.4843 | 0.5312 | 24000 | | 5610 | 8300 | 8770 | | 10000 | | |

| Bearing Dimensions | | | | Shaft | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|---|-----------------------------------|--|--|--|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽¹⁾ | Outer Ring Flange O.D. D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽¹⁾ | Seating Shoulder Dia. d ₁ | Seating Shoulder Dia. D ₁ | G ₁ | G ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | | | | lbs. |
| 23.698 | 17.462 | 2.2 | 93.027 | 9.355 | 2.2 | 56.8 | 57.9 | 86.8 | 22.9 | 0.7 | 0.2889 |
| 0.9330 | 0.6875 | 0.09 | 3.6983 | 0.2187 | 0.09 | 2.26 | 2.24 | 3.39 | | | 1.56 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952336848 |
| Diámetro interior | 41.275 mm |
| Diámetro interior | 1 5/8" inch |
| Diámetro exterior | 88.5 mm |
| Diámetro exterior | 3.484" inch |
| Espesor | 23.698 mm |
| Espesor | 0.933" inch |
| Peso | 710 g |
| Envasado | 1 |
| Estándar | Ninguna norma |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE