

Rodamiento conico

X30310M-Y30310RM-TIMKEN - X30310M-Y30310RM-TIMKEN

https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/x30310m-y30310rm-timken

TAPERED ROLLER BEARINGS

TYPE TSF

Bearing Dimensions				Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic ⁽¹⁾ C ₁	Factors ⁽²⁾ e	Dynamic ⁽¹⁾ C ₂	Factors ⁽²⁾ e	Static C ₀	Inner	Outer		
mm	mm	mm	N		N		N				
50	110	27	14500	2.3	35500	22700	15800	X30310M	Y30310RM		
1.9685	4.3307	1.0629	34000		8900	5110	36000				

Bearing Dimensions						Shaft			Housing		Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a ⁽³⁾	Outer Ring Range D ₁	Flange Width C ₁	Max Shaft Fillet Radius R ⁽⁴⁾	Seating Shoulder Dia. d _s	Seating Shoulder Dia. d _s	Seating Shoulder Dia. D _s	G ₁	G ₂	C ₃		kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm						
27	23	-4.1	116.000	5.000	2.5	51.0	51.0	106.0	10.0	11.5	0.0007		1.36	
1.0629	0.9055	-0.24	4.5669	0.1969	0.10	2.00	2.00	4.17					2.87	

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952337470
Diámetro interior	50 mm
Diámetro exterior	110 mm
Espesor	27 mm
Peso	500 g
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE