

Rodamiento conico 368A-362AB-TIMKEN - 368A-362AB-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/368a-362ab-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|--|-------------------------------|--|---|----------------------------|---|-------|-------|--|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e Y | Dynamic ⁽¹⁾ C ₂ | Static ⁽¹⁾ C ₀ | Factor ⁽³⁾ K | Static ⁽¹⁾ C ₀ | Inner | Outer | | | |
| mm | mm | mm | N | | N | N | | N | | | | | |
| 58 | 88.9 | 22.225 | 102000 | 0.12 | 1.8 | 20400 | 1440 | 10500 | 368A | 362AB | | | |
| 2.000 | 3.500 | 0.875 | 22000 | | 5000 | 5200 | 1.83 | 21000 | | | | | |

| Bearing Dimensions | | | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|----------------|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽⁴⁾ | Outer Ring Range D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁵⁾ | Seating Shoulder Dia. d ₁ | Seating Shoulder Dia. d ₂ | Seating Shoulder Dia. D ₁ | D ₂ | D ₃ | C ₁ | C ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | lbm |
| 22.225 | 16.513 | -4.3 | 83.662 | 4.262 | 3.3 | 56.6 | 62.8 | 66.8 | 33.8 | 14.6 | 0.0773 | 0.59 | 0.59 | 1.18 |
| 0.875 | 0.650 | -0.17 | 3.2875 | 0.1675 | 0.14 | 2.20 | 2.44 | 2.63 | | | | | | |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952337654 |
| Diámetro interior | 50.8 mm |
| Diámetro exterior | 88.9 mm |
| Espesor | 22.225 mm |
| Peso | 530 g |
| Envasado | 1 |
| Estándar | Ninguna norma |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE