


## Rodamiento conico 6464-6420-B-TIMKEN - 6464-6420-B-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/6464-6420-b-timken>

**TAPERED ROLLER BEARINGS**

**TYPE TSF**



| Bearing Dimensions |           |            |   |                             |      | Load Ratings                              |                            |                          |       |        |  | Part Number |  |
|--------------------|-----------|------------|---|-----------------------------|------|---|----------------------------|--------------------------|-------|--------|--|-------------|--|
| Bore<br>d          | O.D.<br>D | Width<br>B | Dynamic <sup>(1)</sup><br>C <sub>10</sub> | Factors <sup>(2)</sup><br>e | Y    | Dynamic <sup>(1)</sup><br>C <sub>90</sub> | Factor <sup>(3)</sup><br>K | Static<br>C <sub>0</sub> | Inner | Outer  |  |             |  |
| mm                 | mm        | mm         | N   |                             |      | N   |                            | N                        |       |        |  |             |  |
| 64.96              | 149.225   | 54.229     | 411000                                    | 0.30                        | 1.91 | 107000                                    | 50000                      | 143000                   | 6464  | 6420 B |  |             |  |
| 2.5575             | 5.8750    | 2.1350     | 17160                                     | 0.0040                      |      | 24000                                     | 16000                      | 194000                   |       |        |  |             |  |

| Bearing Dimensions |            |                               |                                    |                                   |  |  |  |  |                | Geometry Factors |                 |  | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|------------------|-----------------|--|----------------|
| Width<br>B         | Width<br>C | Eff. Ctr.<br>a <sup>(4)</sup> | Outer Ring<br>Range D <sub>1</sub> | Flange<br>Width<br>C <sub>1</sub> | Max Shaft<br>File Radius<br>R <sup>(5)</sup> | Sealing<br>Shoulder Dia.<br>d <sub>1</sub> | Sealing<br>Shoulder Dia.<br>d <sub>2</sub> | Housing<br>Shoulder Dia.<br>D <sub>1</sub> | D <sub>1</sub> | D <sub>2</sub>   | C <sub>10</sub> |  | kg             |
| mm                 | mm         | mm                            | mm                                 | mm                                | mm   | mm   | mm   | mm   | mm             | mm               |                 |  | mm             |
| 54.229             | 44.450     | -15.0                         | 107.060                            | 7.500                             | 3.5  | 61.0                                       | 67.0                                       | 149.225                                    | 156.0          | 28.1             | 0.2001          |  | 4.96           |
| 2.1350             | 1.7500     | -0.59                         | 4.1929                             | 0.2925                            | 0.14   | 2.39                                       | 2.62                                       | 5.91                                       |                |                  |                 |  | 19.78          |

### CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | TIMKEN        |
| Nº Ean13          | 3663952338446 |
| Diámetro interior | 64.96 mm      |
| Diámetro exterior | 149.225 mm    |
| Espesor           | 54.229 mm     |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE