

Rodamiento conico 567A-563-B-TIMKEN - 567A-563-B-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/567a-563-b-timken>

TAPERED ROLLER BEARINGS

TYPE TSF

| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|-------------------------------------------|-----------------------------------------|-----------------------------|-------------------------------------------|-----------------------------------------|----------------------------|--------------------------|-------------|-------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁₀ | Static ⁽¹⁾ C ₀ | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C ₉₀ | Static ⁽¹⁾ C ₀ | Factor ⁽³⁾ K | Static C ₀ | Inner | Outer |
| mm | mm | mm | N | N | | N | N | | N | | |
| 71.437 | 127.000 | 14.288 | 126000 | 44100 | 0.35 | 30900 | 31300 | 1.81 | 26200 | 567A | 563-B |
| 2.8125 | 5.0000 | 0.5625 | | | | 11400 | 11300 | | 38900 | | |

| Bearing Dimensions | | | | Shaft | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|---------------------------------------------|-----------------------------------|----------------------------------------------|--------------------------------------------|--------------------------------------------|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽⁴⁾ | Outer Ring Flange O.D. D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁵⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. D ₁ | G ₁ | G ₂ | C ₂ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | | | | lbs. |
| 36.170 | 28.375 | -4.1 | 123.240 | 6.350 | 3.3 | 86.0 | 125.8 | 101.3 | 24.6 | 0.1167 | 1.56 |
| 1.4240 | 1.1250 | -0.32 | 5.2480 | 0.2500 | 0.14 | 3.15 | 3.38 | 4.78 | | | 4.23 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952338774 |
| Diámetro interior | 71.437 mm |
| Diámetro exterior | 127 mm |
| Espesor | 36.17 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE