

Rodamiento conico 495-493-B-TIMKEN - 495-493-B-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/495-493-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF

| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|---|-----------------------------|------|---|-----------------------------|--------------------------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁₀ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₉₀ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | | N | | N | | | |
| 82.550 | 136.525 | 13.475 | 154000 | 0.14 | 1.30 | 40000 | 3000 | 21000 | 405 | 405-B | |
| 3.250 | 5.375 | 0.5305 | 24700 | | | 9000 | 660 | 46000 | | | |

| Bearing Dimensions | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|--|-----------------------------------|--|--|--|--|------------------|----------------|-----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ D ₂ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₁₀ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | lbs. |
| 29.769 | 22.225 | -4.8 | 141.960 | 5.537 | 3.5 | 96.0 | 97.0 | 125.0 | 104.6 | 29.3 | 0.1252 | 1.67 |
| 1.1720 | 0.8750 | -0.03 | 5.5980 | 0.2180 | 0.14 | 3.74 | 3.82 | 4.91 | | | | 3.68 |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952339139 |
| Diámetro interior | 82.55 mm |
| Diámetro exterior | 136.525 mm |
| Espesor | 29.769 mm |
| Envasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE