


Rodamiento conico 42368-42587-B-TIMKEN - 42368-42587-B-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/42368-42587-b-timken>

TAPERED ROLLER BEARINGS

TYPE TSF



| Bearing Dimensions | | | Load Ratings | | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|------|--|-----------------------------|--------------------------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₂ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | | N | | N | | | |
| 93.662 | 149.225 | 28.971 | 10200 | 0.14 | 1.22 | 98100 | 4200 | 24100 | 42368 | 42587-B | |
| 3.6875 | 5.8750 | 1.1300 | 43400 | | | 11300 | 9400 | 94300 | | | |

| Bearing Dimensions | | | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|----------------|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₁ | C ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | lbs. |
| 28.971 | 28.968 | 3.0 | 154.691 | 5.599 | 3.0 | 102.0 | 107.0 | 152.0 | 129.7 | 27.2 | 0.1385 | 1.96 | 4.38 | |
| 1.1406 | 1.1406 | 0.12 | 6.0989 | 0.2198 | 0.12 | 4.02 | 4.21 | 5.99 | | | | | | |

CARACTERÍSTICAS DEL PRODUCTO

| | |
|-------------------|---------------|
| Marca | TIMKEN |
| Nº Ean13 | 3663952339450 |
| Diámetro interior | 93.662 mm |
| Diámetro exterior | 149.225 mm |
| Espesor | 28.971 mm |
| Invasado | 1 |

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE