

## Rodamiento conico

### M244249A-M244210-B-TIMKEN - M244249A-M244210-B-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/m244249a-m244210-b-timken>

**TAPERED ROLLER BEARINGS**

**TYPE TSF**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factors <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factors <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
220.662 8.6875	314.325 12.3750	22.225 0.8750	64000 140000	0.33 1.10	158000 37000	9900 21500	1700 124000	M244249A	M244210-B	

  

Bearing Dimensions			Shaft			Housing			Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a <sup>(1)</sup>	Outer Ring Range O.D. D <sub>1</sub>	Flange Width C <sub>1</sub>	Max Shaft File Radius R <sup>(1)</sup>	Sealing Shoulder Dia. d <sub>1</sub>	Sealing Shoulder Dia. d <sub>2</sub>	Sealing Shoulder Dia. D <sub>1</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm				lbm
22.225 0.8750	48.212 1.9375	-4.6 -0.18	323.800 12.7500	9.525 0.3750	1.5 0.06	226.0 8.92	226.0 8.92	308.8 11.81	1073.1	132.4	0.1307	15.28 33.70

## CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952340456
Diámetro interior	220.662 mm
Diámetro interior	8 11/16" inch
Diámetro exterior	314.325 mm
Diámetro exterior	12 3/8" inch
Espesor	66.675 mm
Espesor	2 5/8" inch
Peso	0.0001 g
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE