


Rodamientos a rótula de bola 1214-K-TVH-C3-H214-FAG - 1214-K-TVH-C3-H214-FAG

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/rotula/1214-k-tvh-c3-h214-fag>

Self-aligning ball bearings 1214-K-TVH-C3 + H214
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve



d_{int}	60 mm
D	125 mm
B	24 mm
B_{min}	5 mm
c	14 mm
D ₁	106.6 mm
D _{1max}	116 mm
D ₂	92 mm
d	70 mm
d ₁	87.7 mm
d _{1max}	79 mm
d _{2min}	75 mm
l	41 mm
f _{tmax}	1.8 mm
H214	Mass, adapter sleeve
m	1.23 kg Mass
m _{H214}	0.63 kg Mass, adapter sleeve
C	35000 N Basic dynamic load rating, radial
e	0.19
Y ₁	3.36
Y ₂	5.21
C ₁₀	13700 N Basic static load rating, radial
Y ₀	3.52
n ₀	6000 1/min Limiting speed
n _B	7900 1/min Reference speed
C _r	800 N Fatigue limit load, radial

CARACTERÍSTICAS DEL PRODUCTO

Marca	FAG
Nº Ean13	3663952346250
Diámetro interior	60 mm
Diámetro exterior	125 mm
Espesor	24 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE