



Rodamientos a rótula de bola

1218-K-TVH-C3-H218-FAG - 1218-K-TVH-C3-H218-FAG

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-bola/rotula/1218-k-tvh-c3-h218-fag>

Self-aligning ball bearings 1218-K-TVH-C3 + H218
main dimensions to DIN 630 and DIN 5415, with tapered bore and adapter sleeve

d_{int}	80 mm
D	160 mm
B	30 mm
$B_{s,min}$	6 mm
c	18 mm
D_1	136,7 mm
$D_{s,max}$	149 mm
D_{ext}	120 mm
d	90 mm
d_1	112,7 mm
$d_{s,max}$	101 mm
$d_{2,min}$	90 mm
l	82 mm
$f_{s,max}$	2 mm
$H218$	Mass, adapter sleeve
m	2,48 kg Mass
m_s	1,21 kg Mass, adapter sleeve
C	57000 N Basic dynamic load rating, radial
s	0,17
Y_1	3,74
Y_2	5,79
C_{10}	23300 N Basic static load rating, radial
Y_3	3,92
n_0	4300 1/min Limiting speed
n_B	6600 1/min Reference speed
C_{10}	1300 N Fatigue limit load, radial

CARACTERÍSTICAS DEL PRODUCTO

Marca	FAG
N° Ean13	3663952346298
Diámetro interior	80 mm
Diámetro exterior	160 mm
Espesor	30 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE