


Casquillos de agujas YT1715-IKO - YT1715-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/yt1715-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identificación number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g	
17	---	---	---	---	---	---	---	---	---	YT 1715	20.5

Boundary dimensions mm				Standard mounting dimensions mm						Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	f ₂ Max.	Shaft dia. h6		Housing bore dia. H7		N7		C	C ₀	N	rpm	IRT 1215-2
				Max.	Min.	Max.	Min.	Max.	Min.					
17	24	15	---	17.000	16.989	24.012	23.991	---	---	16 600	26 000	9 000		

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952353135
Diámetro interior	17 mm
Diámetro exterior	24 mm
Espesor	15 mm
Peso	22 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE