

Rodamiento conico 32221-TIMKEN - 32221-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/32221-timken>

TAPERED ROLLER BEARINGS
SINGLE-ROW • IsoClass

IsoClass

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C ₁	Factor ⁽²⁾ e	Dynamic ⁽³⁾ C ₂	Factor ⁽²⁾ K	Static C ₀	Assembly Inner/Outer		
mm	mm	mm	N		N		N			
in	in	in	lbf		lbf		lbf			
102.000	190.000	53.000	20000	4.42	12000	14300	1.20	57000	32221	
4.1339	7.4803	2.0866	89000		22000	16100		116000		

Mounting Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G ₁	G ₂		C ₃
Width B	Width C	ER Co. g ⁽⁴⁾	Max Shaft Fillet Radius R ⁽⁵⁾	Backing Shoulder Dia. d _s	Max Housing Fillet Radius r ⁽⁶⁾	Backing Shoulder Dia. D _s	Backing Shoulder Dia. D ₂	A ₁ ⁽⁷⁾	A ₂ ⁽⁸⁾				G ₁	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	lb
50.000	45.000	-7.9	3.0	120.0	127.0	2.5	190.0	171.0	5.1	2.7	219.9	43.9	0.1002	5.94
1.9685	1.7715	-0.31	0.12	4.72	5.00	0.10	7.50	6.73	0.20	0.11				13.08

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952353920
Diámetro interior	105 mm
Diámetro exterior	190 mm
Espesor	53 mm
Peso	5940 g
Envasado	1
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE