

Rodamiento conico 395-S-394D-TIMKEN - 395-S-394D-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/395-s-394d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic ⁽¹⁾ C ₁₀	Static ⁽¹⁾ C ₀	Dynamic ⁽²⁾ Y ₁	Dynamic ⁽²⁾ Y ₂	Dynamic ⁽³⁾ C ₉₀	Dynamic ⁽³⁾ C ₅₀	Dynamic ⁽³⁾ C ₁₀₀	Factor ⁽⁴⁾ K
mm	mm	mm	mm	N	N	N	N	N	N	N	
66.675	110.000	52.388	46.838	32000	40000	0.40	1.68	2.50	25600	17800	1.45
2.6250	4.3307	2.0625	1.8125	38700	48700				5700	3970	

Part Number		Dimensions					Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R ₁	Backing Shoulder Dia. d ₁	Max. Housing Fillet Radius r ₁	Backing Shoulder Dia. D ₁	K ₁	K ₂	G ₁	G ₂	C ₁	kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
395-S	394D	3.5 0.14	29.0 3.11	0.8 0.05	106.4 4.11	-	-	50.0	21.4	0.0984	1.26 3.88	

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952357164
Diámetro interior	66.675 mm
Diámetro exterior	110 mm
Espesor	52.388 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE