

Casquillos de agujas TA6030-Z-IKO - TA6030-Z-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/ta6030-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS

Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
60	TA 6030 Z	191	—	—	—	—	—	—	—	—

Boundary dimensions mm	Standard mounting dimensions mm						Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Shaft dia. H7	Shaft dia. k6	Housing bore dia. H7	Housing bore dia. k7	Housing bore dia. N7	Housing bore dia. N7				
F _w D C	Max. Min.	Max. Min.	Max. Min.	Max. Min.	Max. Min.	N	N	rpm	IRT 5030	
60 72 30	3.4 60.000 59.981	72.018 71.988	— —	— —	— —	66 300	139 000	5 000	IRT 5030	

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952357409
Diámetro interior	60 mm
Diámetro exterior	72 mm
Espesor	30 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE