

Casquillos de agujas TAW6045-Z-IKO - TAW6045-Z-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/taw6045-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS

Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
60	TAW 6045 Z	270	—	—	—	—	—	—	—

Boundary dimensions mm	Standard mounting dimensions mm						Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ^(*) rpm	Assembled inner ring				
	Shaft dia. H7	Shaft dia. h8	Housing bore dia. H7	Housing bore dia. h7	Housing bore dia. H7	Housing bore dia. h7								
F _w D C i ₂ Max.	60	72	45	3.4	60.000	59.981	72.018	71.988	—	—	85 400	193 000	5 000	IRT 5045

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952357423
Diámetro interior	60 mm
Diámetro exterior	72 mm
Espesor	45 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE