


Casquillos de agujas TAW6550-Z-IKO - TAW6550-Z-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/taw6550-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
65	TAW 6550 Z	330	—	—	—	—	—	—	—	—

Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring		
F _w	D	Shaft dia. h8		Housing bore dia. H7		N7	N	N	rpm	IRT 5550			
		Max.	Min.	Max.	Min.	Max.	Min.	Min.	Min.				
65	77	50	3.4	65.000	64.981	77.018	76.988	—	—	101 000	246 000	4 000	IRT 5550

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952357515
Diámetro interior	65 mm
Diámetro interior	2.559" inch
Diámetro exterior	77 mm
Diámetro exterior	3.031" inch
Espesor	45 mm
Espesor	1.772" inch
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE