

Rodamiento conico 567A-563D-TIMKEN - 567A-563D-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/567a-563d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic ⁽¹⁾		Static ⁽²⁾		Dynamic ⁽³⁾		Factor ⁽⁴⁾	
mm	mm	mm	mm	C ₁₀	N	C ₀	N	C ₁₀	N	C ₀	K
71.437	127.000	80.962	65.988	362000	18000	0.30	1.86	2.78	30900	31700	8800
2.8125	5.0000	3.1875	2.5825	18000	9000				11400	7130	1900

Part Number		Dimensions						Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R ₁	Backing Shoulder Dia. d ₁	Max. Housing Fillet Radius r ₁	Backing Shoulder Dia. D ₁	K ₁	K ₂	G ₁	G ₂	C ₁			
567A	563D	3.5 0.14	80.0 3.20	1.5 0.06	116.0 4.60	-	-	103.3	24.0	0.1167	4.82 8.88		

CARACTERÍSTICAS DEL PRODUCTO

Marca	TIMKEN
Nº Ean13	3663952357775
Diámetro interior	71.437 mm
Diámetro exterior	127 mm
Espesor	80.962 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE