


Casquillos de agujas YB45-IKO - YB45-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/yb45-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard			Mass (Ref.) g		
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained g	Mass (Ref.) g
6.350 (1/4)	—	—	—	YB 45	3.2	—	—	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	C	C_0	rpm	
6.350 (1/4)	11.112 (7/16)	7.92 (3/16)	6.350 Max.	6.341 Min.	11.122 Max.	11.104 Min.	4 450	4 870	25 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952361215
Diámetro interior	6.35 mm
Diámetro interior	1/4" inch
Diámetro exterior	11.112 mm
Diámetro exterior	7/16" inch
Espesor	7.92 mm
Espesor	0.312" inch
Peso	1 g
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE