


Casquillos de agujas YB68-IKO - YB68-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/yb68-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard Mass (Ref.) g	Closed end Mass (Ref.) g	Standard Mass (Ref.) g	Closed end Mass (Ref.) g	Grease retained Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end					
9.525 (3/8)	—	—	—	YB 68	7.2	—	—	—

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring
F _w	D	C	Shaft dia. h8 Max. Min.	Housing bore dia. J7 Max. Min.	mm				
9.525 3/8	14.288 9/16	12.70 1/2	9.525 Max. 9.516 Min.	14.288 Max. 14.280 Min.	9 210	13 600	16 000	—	

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952361253
Diámetro interior	9.525 mm
Diámetro interior	3/8" inch
Diámetro exterior	14.288 mm
Diámetro exterior	9/16" inch
Espesor	12.7 mm
Espesor	1/2" inch
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE