



Casquillos de agujas BHAM1212-IKO - BHAM1212-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bham1212-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g																																																									
	Standard	Mass (Ref.) g	Closed end																																																																			
19.050 ($\frac{3}{8}$)	—	—	—	—	—	—	—	—	—	—	—	—	—																																																									
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="2">mm(inch)</th> <th colspan="4">Standard mounting dimensions</th> <th colspan="2">mm</th> <th colspan="2">Basic dynamic load rating</th> <th colspan="2">Basic static load rating</th> <th colspan="2">Allowable rotational speed⁽¹⁾</th> <th colspan="2">Assembled inner ring</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>B_2</th> <th>Shaft dia. ϕ_6</th> <th>Housing bore dia. J_7</th> <th>C</th> <th>C_0</th> <th>C_0</th> <th>C_0</th> <th>N</th> <th>N</th> <th>N</th> <th>N</th> <th>rpm</th> <th colspan="2"></th> <th colspan="2"></th> </tr> </thead> <tbody> <tr> <td>19.050 ($\frac{3}{8}$)</td> <td>26.988 ($1\frac{1}{8}$)</td> <td>19.050 ($\frac{3}{4}$)</td> <td>1.3</td> <td>19.050</td> <td>19.037</td> <td>27.000</td> <td>26.979</td> <td>16 800</td> <td>22 600</td> <td>20 000</td> <td colspan="2">IRB 812-1</td> <td colspan="2"></td> <td colspan="2"></td> <td colspan="2"></td> </tr> </tbody> </table>														Boundary dimensions			mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring		F_w	D	C	B_2	Shaft dia. ϕ_6	Housing bore dia. J_7	C	C_0	C_0	C_0	N	N	N	N	rpm					19.050 ($\frac{3}{8}$)	26.988 ($1\frac{1}{8}$)	19.050 ($\frac{3}{4}$)	1.3	19.050	19.037	27.000	26.979	16 800	22 600	20 000	IRB 812-1							
Boundary dimensions			mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring																																																					
F_w	D	C	B_2	Shaft dia. ϕ_6	Housing bore dia. J_7	C	C_0	C_0	C_0	N	N	N	N	rpm																																																								
19.050 ($\frac{3}{8}$)	26.988 ($1\frac{1}{8}$)	19.050 ($\frac{3}{4}$)	1.3	19.050	19.037	27.000	26.979	16 800	22 600	20 000	IRB 812-1																																																											

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952361819
Diámetro interior	19.05 mm
Diámetro exterior	26.988 mm
Espesor	19.05 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE