


Casquillos de agujas BHAM1412-IKO - BHAM1412-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bham1412-iko>



Shaft dia. mm (inch)	Identification number			Identification number			Grease retained Mass (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
22.225 (7/8)	---	---	---	---	---	BHAM 1412	32.5	---

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
F_w	D	C	Shaft dia. ϕ	Housing bore dia. $J7$	Shaft dia. ϕ	Housing bore dia. $J7$	C	C_0			
22.225	30.162	19.05	22.225	22.212	30.176	30.151	18 000	26 100	18 000	IRB 1012	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952361871
Diámetro interior	22.225 mm
Diámetro exterior	30.162 mm
Espesor	19.05 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE