

## Casquillos de agujas BHAM1614-IKO - BHAM1614-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bham1614-iko>

Shaft dia. mm (inch)	Standard			Closed end			Mass (Ref.) g			Grease retained g
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g		
25.400 (1)	—	—	—	—	—	—	—	—	—	—

  

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
F <sub>w</sub>	D	B	Shaft dia. d <sub>h</sub>	Housing bore dia. J7	Max.	Min.				
25.400	33.338	22.22	25.400	25.387	33.352	33.327	23 000	37 200	15 000	IRB 1214

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952362021
Diámetro interior	25.4 mm
Diámetro exterior	33.338 mm
Espesor	22.22 mm
Envasado	1

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE