

Casquillos de agujas
BHAM1616-IKO - BHAM1616-IKO

https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/bham1616-iko



BAM BHAM

Shaft dia. mm (inch)	Identification number			Shaft dia. mm (inch)	Housing bore dia. mm (inch)	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end						
25.400 (1)	—	—	—	—	—	—	—	—	—
Boundary dimensions mm(inch)									
F _w	D	C	h _s	Max.	Min.	Max.	Min.	N	N
25.400	33.338	25.40	3.4	25.400	25.387	33.352	33.327	26 400	44 500

Notes⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952362038
Diámetro interior	25.4 mm
Diámetro exterior	33.338 mm
Espesor	25.4 mm
Envasado	1

contacto@123rodamiento.es
911 436 830
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE