


Casquillos de agujas YB1816-IKO - YB1816-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/yb1816-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
28.575 (1 1/8)	—	—	—	—	—	—	—	—	—	—	—	YB 1816	51.5
Boundary dimensions		mm(inch)		Standard mounting dimensions		mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾	
F_w	D	C	f_d	Shaft dia. h6	Housing bore dia. J7	C	C_0	C	C_0	C_0	C_0	C_0	C_0
28.575 (1 1/8)	34.925 (1 3/8)	25.40 (1.000)	—	28.575 Max. 28.562 Min.	34.939 Max. 34.914 Min.	38 700 N	90 400 N	5 500 rpm	IRB 1416				

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952362083
Diámetro interior	28.575 mm
Diámetro exterior	34.925 mm
Espesor	25.4 mm
Peso	53 g
Envasado	-
Estándar	Ninguna norma

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE