


Casquillos de agujas YB2416-IKO - YB2416-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/yb2416-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g						
	Standard	Mass (Ref.) g	Closed end																
38.100 (1 1/2)	—	—	—	—	—	—	—	—	—	—	—	YB 2416	105						
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed ⁽¹⁾		Assembled inner ring			
F_w		D		C		t		Shaft dia. mm		Housing bore dia. mm		C		C_0		rpm		IRB 2016	
38.100 (1 1/2)		47.625 (1 7/8)		25.40 (1.000)		—		38.100 38.084 47.639 47.614		55 100 118 000		4 000		—		—		—	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952363110
Diámetro interior	38.1 mm
Diámetro exterior	47.625 mm
Espesor	25.4 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE