


Casquillos de agujas YB2420-IKO - YB2420-IKO

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-agujas/casquillos-agujas/yb2420-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
38.100 (1 1/2)	—	—	—	—	—	—	—	—	—	—	—	YB 2420	131
Boundary dimensions		mm(inch)		Standard mounting dimensions				mm		Basic dynamic	Basic static	Allowable	Assembled
F_w	D	C	t	Shaft dia. mm	Housing bore dia. mm	Max.	Min.	Max.	Min.	C	C_0	rotational speed ⁽¹⁾	inner ring
38.100	47.625	31.75	—	38.100	38.084	47.639	47.614	66 900	151 000	4 000	IRB 2020		

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DEL PRODUCTO

Marca	IKO
Nº Ean13	3663952363127
Diámetro interior	38.1 mm
Diámetro exterior	47.625 mm
Espesor	31.75 mm
Envasado	1

contacto@123rodamiento.es

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE