


## Rodamiento conico

### LM119348D-LM119311-TIMKEN - LM119348D-LM119311-TIMKEN

<https://www.123rodamiento.es/rodamiento-cojinete/rodamiento-rodillos/conico/lm119348d-lm119311-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDI

**TYPE TDI**



| Bearing Dimensions |         |         |                           | Load Ratings                          |                                     |                                     |                                     |                                       |                                       |  |                        |      |
|--------------------|---------|---------|---------------------------|---------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|---------------------------------------|---------------------------------------|--|------------------------|------|
| Bore d             | O.D. D  | Width T | Double Inner Ring Width B | Dynamic <sup>CR</sup> C <sub>10</sub> | Static <sup>CR</sup> C <sub>0</sub> | Factor <sup>CR</sup> Y <sub>1</sub> | Factor <sup>CR</sup> Y <sub>2</sub> | Dynamic <sup>CR</sup> C <sub>90</sub> | Dynamic <sup>CR</sup> C <sub>50</sub> | Dynamic <sup>CR</sup> C <sub>100</sub> | Factor <sup>CR</sup> K |      |
| mm                 | mm      | mm      | mm                        | N                                     | N                                   | N                                   | N                                   | N                                     | N                                     | N                                      |                        |      |
| 95.250             | 136.525 | 57.150  | 57.150                    | 36300                                 | 36200                               | 0.3                                 | 2.4                                 | 3.5                                   | 30200                                 | 17600                                  | 63000                  | 2.06 |
| 3.750              | 5.3750  | 2.2500  | 2.2500                    | 9000                                  | 8140                                |                                     |                                     |                                       | 3950                                  | 14200                                  |                        |      |

| Part Number |          | Dimensions                             |                                      |  |                                      | Geometry Factors |                |                | Bearing Weight |
|-------------|----------|--|--------------------------------------|--|--------------------------------------|------------------|----------------|----------------|----------------|
| Inner       | Outer    | Max Shaft Fillet Radius r <sub>1</sub> | Backing Shoulder Dia. d <sub>s</sub> | Max Housing Fillet Radius r <sub>2</sub> | Backing Shoulder Dia. D <sub>s</sub> | G <sub>1</sub>   | G <sub>2</sub> | C <sub>3</sub> | kg             |
| mm          | mm       | mm                                     | mm                                   | mm                                       | mm                                   |                  |                |                | lbm            |
| LM119348D   | LM119311 | 0.8                                    | 102.8                                | 2.3                                      | 136.8                                | 148.4            | 84.1           | 0.1213         | 0.88           |
|             |          | 0.03                                   | 4.02                                 | 0.03                                     | 4.96                                 |                  |                |                | 5.91           |

## CARACTERÍSTICAS DEL PRODUCTO

|                   |               |
|-------------------|---------------|
| Marca             | TIMKEN        |
| Nº Ean13          | 3663952368603 |
| Diámetro interior | 95.25 mm      |
| Diámetro exterior | 136.525 mm    |
| Espesor           | 57.15 mm      |
| Envasado          | 1             |

[contacto@123rodamiento.es](mailto:contacto@123rodamiento.es)

911 436 830

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE